

# AQ211 - Comprehensive portable air quality logger with internet connectivity

# Eltek

SPECIALIST DATA LOGGERS

AQ211 is an advanced air quality logger with internet connectivity via the 4G LTE-M and NB-IoT networks. It enables detailed monitoring of a site such as a school, hospital, office, gallery, or work area - anywhere that air pollution can affect the health of the occupants or the objects and processes within.

## System Operation

A single box solution with the following built in gas and air particulate sensors:

### CO<sub>2</sub>

Range: 0-5000ppm  
Accuracy at +25 °C:  $< \pm (50\text{ppm} + 3\% \text{ of measured value})$  at 1013mBar

Temperature dependence: Typically 2ppm CO<sub>2</sub> / °C over the range 0 to +50°C  
Pressure dependence: 0.14% of measured value / mBar deviation

### Relative Humidity

Range: 0-100% non condensing  
Accuracy:  $\pm 2\%$  (10 to 90% RH)  
 $\pm 4\%$  (0 to 100% RH)  
Resolution: 0.1%

### Temperature

Range: -20°C to 70°C  
Accuracy:  $\pm 0.4^\circ\text{C}$  (-5°C to 40°C)  
 $\pm 1.0^\circ\text{C}$  (-20°C to 65°C)  
 $\pm 0.5^\circ\text{C}$  (5°C to 45°C)  
Resolution: 0.1°C

### CO

Range: -5.00-500.00ppm

### NO<sub>2</sub>

Range: -0.1000-3.0000ppm

### O<sub>3</sub>

Range: -0.1000-3.0000ppm

### VOC

Range: 0-50ppm

### Particulates (Air flow 0 to 5 L/minute)

3 channels: PM1 0-1  $\mu\text{m}$  sized particles ( $\mu\text{g}/\text{m}^3$ )  
PM2.5 0-2.5  $\mu\text{m}$  sized particles ( $\mu\text{g}/\text{m}^3$ )  
PM10 0-10  $\mu\text{m}$  sized particles ( $\mu\text{g}/\text{m}^3$ )

For workplace atmospheres (ref. BSEN481)

the transmitter may be set to log up to 1,005,000 readings and optionally upload values directly to Darca Connect



## Specification

Dimensions:	120mm x 85mm x 200mm (380mm with aerial)
Weight:	820g
Case material:	Polycarbonate
Antenna socket:	SMA
Antenna type:	LTE Swivel Blade SMA
Power supply:	Mains AC with battery backup
Power supply type:	MP12U (12VDC/0.8A)
Power connector (12VDC):	2.1mm barrel jack
Battery backup:	24 Hours
Battery chemistry:	Li-ion
Time to charge:	8 hours
Environmental rating:	IP20
Operating temperature:	-10 to +55°C
Operating Humidity:	0-90%RH non condensing
RF compliant to:	EN301 489-1, EN301 908-1
Frequency Channels	1,2,3,4,5,8,12,13,14,18,19, 20,25,26,27,28,66,85
Modes of operation:	LTE CATM-1/NB-IoT locale specific

Due to our policy of continuous improvement specifications may change without prior notice. Eltek believes that all information declared is correct at the time of issue, no liability is accepted for errors and omissions.



**Guarantee** Equipment manufactured by Eltek is guaranteed against faulty materials or workmanship for three years. For repairs carried out under guarantee, no charge is made for labour, materials or return carriage.



## Eltek

Specialist Data Loggers  
Eltek Ltd, 35 Barton Road, Haslingfield  
Cambridge, CB23 1LL, England  
Tel: +44 (0) 1223 872111  
email: [sales@eltekdataloggers.co.uk](mailto:sales@eltekdataloggers.co.uk)  
<http://www.eltekdataloggers.co.uk>